

BODO MÖLLER CHEMIE

Engineer chemistry

Your reliable partner for
adhesive bonding

Adhesive laboratory

Test methods



Standard laboratory ageing conditions for testing adhesive connections

The most appropriate method accelerated aging will depend on the type of adhesive and adherent material, and the intended use of the adhesive joint. In general, stimulatory aging methods are used in which the aging conditions attempt to simulate natural conditions, usually with only a moderate acceleration of the factors. For examples of aging methods include: heat aging, water resistance, freeze-thaw, corrosion and chemical resistance, artificial weathering. The ageing conditions are applicable to bonded assemblies and may be used to constitute a set of tests for the evaluation of an adhesive. For general applications, the following overview may serve to suggest accelerating aging cycles as being both applicable and relevant to the major mechanism of degradation.

Exposure to moisture (cataplasm test)

Aging at extreme humidity and 70°C for 7 or 14 days, depending on the intended application.

Exposure to water and other liquids

Immersion on 20, 23, 40, 60 or 80°C for typically 150 to 1500h, depending on the intended application. Note that this type of exposure simulates degradation under elevated temperature and high humidity, but does not promote corrosive attack due to the lack of oxygen in the immersion bath unless constantly aerated.

Aging on elevated temperature

Aging on elevated temperature in the absence of moisture especially promotes oxidation, embitterment and thermal degradation. Typical temperatures depend on the intended application. For adhesive bond under outside weathering temperatures of 80–120°C are common, depending on geographical area of application.

Thermal cycling

Accelerated aging tests under cyclic change of temperature include the freeze-thaw transition to consider the detrimental effect of water penetration and icing. Temperatures typically span from -20 or -40°C to 60 or 80°C with 95% relative humidity during the warm period of the cycles. Typical number of cycles range from 100 to 300h. It should be considered that rapid transitions between high and low temperature limits may induce thermal stress beyond levels representative of outside weather conditions, for example.

UV exposure

Climatic chambers with phytotron system are available to simulate aging conditions, combining moisture, temperature and UV radiations. The test duration depends on the irradiation doses to be expected in the specific application, and typically range from 500 to 3000h. Clearly, such tests should mainly be considered if one or both adherents is/are transparent to the applied spectra of radiation.

Salt spray test

The salt spray test is an accelerated corrosion test that produces a corrosive attack to the metal and coated samples. The appearance of corrosion products (oxides) is evaluated after a period of time. Test duration depends on the corrosion resistance of the metal or coating. Standard cabinets for corrosion testing create a salt spray environment at 35°C. Exposure times typically range from 300 to 1000h depending on the intended application.



Equipment



Cyclic corrosion chamber
Ascott CCip 450



Climatic chambers
Binder MKF 240 / Poleco TOP+



Drying ovens
Binder ED 53 / Binder FD 115



Universal testing machine
Zwick Zo50 TN ProLine

UV light aging test chamber
ATLAS UVTest™

Laboratory freezer Fryka B30-40

Temperature and humidity
measurement QMSystem
Module QLabPoll

Viscometer Fungilab
Smart Series L

Precision balance Sartorius
to 4 kg/0.01 g



BODO MÖLLER CHEMIE laboratory

Our laboratory is an independent adhesives and materials R&D, consulting, and testing laboratory, offering a comprehensive knowledge of adhesive technology. It is located in Poland in the High Technology Incubators Complex of Poznań Science and Technology Park of Adam Mickiewicz University Foundation. The High Technology Incubators Complex is the largest laboratory and office complex designed for innovative companies and offering a friendly environment for the development of new technologies.

Our laboratory utilizes a Quality Management System in conformance with ISO 9001:2008 as well as the certificate for manufacturing adhesive bonds in accordance with DIN 2304. Furthermore, the laboratory is certified by TBB Cert according to the DIN 6701 standard for adhesive bonding of railway vehicles and parts. As we fulfill our duty to establish, execute, and evaluate product and regulatory requirements, we do so reinforcing themes of comprehensive planning, reliable reporting, and continual improvement.

Our adhesive testing lab provides you with exceptional precision and versatility to test everything from adhesives and sealants to specialty materials and packaging.



Laboratory
Bodo Möller Chemie Polska Sp. z o.o.
Phone +48 61 6272143
Mobile +48 609 090566
info@bm-chemie.pl

ISO standards

PN-ISO 4588-1999

Guidelines for the surface preparation of metals

PN-EN 13887:2005

Guidelines for surface preparation of metals and plastics prior to adhesive bonding

PN-EN ISO 9142:2005

Guide to the selection of standard laboratory ageing conditions for testing bonded joints

PN-EN ISO 291:2010

Standard atmospheres for conditioning and testing

PN-EN ISO 9227:2012

Corrosion tests in artificial atmospheres – Salt spray tests

PN-EN 13523-27:2010

Test methods: Resistance to humid poultice (Cataplasm test)

PN-EN ISO 10365:1998

Designation of main failure patterns

PN-EN 1465:2009

Determination of tensile lap-shear strength of bonded assemblies

PN-EN 28510-1:2000

Peel Test for a Flexible-Bonded-to-Rigid
Test Specimen Assembly – Part 1: 90 Degree Peel

PN-EN 28510-2:2000

Peel Test for a Flexible-Bonded-to-Rigid
Test Specimen Assembly – Part 2: 180 Degree Peel

PN-EN ISO 11339:2010

T-peel test for flexible-to-flexible bonded assemblies

DIN 6701-2:2006

Adhesive bonding of railway vehicles and parts
Part 2: Qualification of manufacturer of adhesive bonded materials, quality assurance

DVS 1618:2002

Elastic thick layer bonding in rail vehicle construction

DIN 54457:2014

Testing of adhesively bonded joints: Bead peel test

PN-EN ISO 2555:2011

Liquid polymers in form of emulsions or dispersions –
determination of apparent viscosity by the Brookfield test method

PN-EN ISO 4892-1:2001

Methods of exposure to laboratory light sources –
Part 1: General guidance

PN-EN ISO 4892-2:2013

Methods of exposure to laboratory light sources –
Part 2: Xenon-arc lamps

PN-EN ISO 4892-3:2013

Methods of exposure to laboratory light sources –
Part 3: Fluorescent UV lamps

PN-EN ISO 9227:2014

Corrosion tests in artificial atmospheres – Salt spray tests

DIN 2304:2016

Quality requirements for adhesive bonding processes

Test methods and equipment

Determination of mechanical properties

Type of Test & Properties:

Used to determine the tensile strength and more of various materials from metals to plastics

Capacities of 1 kN and of 50 kN

Tension, 90 degree, 180 degree, and T peel adhesion, shear, flexural

Equipment

Zwick Zo50 TN ProLine
with wedge-screw grips-Fmax 50 kN

Determination of thermal properties of adhesives

Differential Scanning Calorimetry (DSC)

Measures other thermal and physical characteristics of polymers: glass transition temperature, melting point, curing efficiency, post-curing effects, phase transitions in thermoplastic polymers, thermal degradation of organic phase, oxidation of thermoplastics, filament content (accuracy of 0,01%), and more. We can also use these chemical analysis techniques to understand the «thermal history» of a material and determine failure modes.

Temperature range: -180°C – 700°C

Heating rates 0.001 K/min – 200 K/min

Thermogravimetric Analysis (TGA)

Measures the mass changes in a material as the sample is slowly heated. We can roughly determine the amount of water, volatiles, and non-volatiles in a sample by this technique.

Temperature range: RT to 1100°C

Equipment

Netzsch 204 F1 Phoenix
Mettler Toledo DSC 1

Equipment

Netzsch TG 209 F1 Libra
Netzsch Jupiter STA 449F3

Determination of thermo-mechanical properties of adhesives

Dynamic Mechanical Analysis (DMA)

Type of Test & Properties

Measures the mechanical properties of materials as a function of time, temperature and frequency. It is most useful for studying the viscoelastic behavior of polymers.

One important application of DMA is measurement of the glass transition temperature under cyclic deformation, measurement of dynamic viscosity in oscillatory mode, storage modulus, loss modulus, viscoelastic behaviour of adhesives vs. temperature and shear rates or deformation amplitude, etc.

Temperature range: -150°C – 450°C

Capillary rheometry has its origins in polymer melt processing. Based on controlled extrusion of a test material, capillary rheometry enables material flow and deformation properties to be characterized under conditions of high force (or pressure), high shear rate and at elevated temperature.

The Melt Flow Indexer can be used for measuring melt volume rate or melt flow rate in research applications and quality control.

The laboratory offers a humidity test, a salt spray test and other analysis.

Equipment

Oscillatory rheometer, dynamic-mechanical thermal analyzer, DMTA apparatus Anton Paar CTD 450

Capillary rheometer Dynisco

Melt Flow Indexer Dynisco

Regional offices

BODO MÖLLER CHEMIE



GERMANY

Bodo Möller Chemie GmbH

Headquarters

Offenbach a. M.

Phone +49 69 838326-0 | info@bm-chemie.de

AUSTRIA

Bodo Möller Chemie Austria GmbH

Vienna

Phone +43 120 51907050 | info@bm-chemie.at

SWITZERLAND

Bodo Möller Chemie Schweiz AG

Winterthur

Phone +41 52 2031930 | info@bm-chemie.ch

FRANCE

Bodo Möller Chemie France SAS

Sales Office Ruaudin

Phone +33 243 240429 | bureau@bm-chemie.fr

Sales Office Lyon

Phone +33 478 982337 | bureaulyon@bm-chemie.fr

BENELUX

Bodo Möller Chemie Benelux N.V.

Kruibeke (Belgium)

Phone +32 3 2352135 | info@bm-chemie.be

SPAIN

Bodo Möller Chemie Spain s.l.

Rivas-Vaciamadrid

Phone +34 916 286909 | info@bm-chemie.es

PORTUGAL

Bodo Moeller Chemie Portugal Unipessoal LDA

Valbom

Phone +351 937 198020 | info@bm-chemie.pt

ITALY

Bodo Möller Chemie Schweiz AG

Succursale Milano

Phone +41 799199904 | info@bm-chemie.ch

UNITED KINGDOM / IRELAND

Bodo Möller Chemie UK Ltd.

Manchester (Great Britain)

Phone +44 161 8042029 | info@bm-chemie.co.uk

DENMARK

Bodo Möller Chemie Denmark Aps

Stenløse

Phone +45 48 163470 | info@bm-chemie.dk

SWEDEN

Bodo Möller Chemie Sweden AB

Källered

Phone +46 31 698952 | info@bm-chemie.se

NORWAY

Bodo Möller Chemie Norway NUF

Oslo

Phone +45 48 16 34 70 | info@bm-chemie.no

FINLAND

Bodo Möller Chemie Finland Oy

Helsinki

Phone +358 9 6829010 | info@bm-chemie.fi

POLAND

Bodo Möller Chemie Polska Sp. z o.o.

Suchy Las

Phone +48 61 8220975 | info@bm-chemie.pl

Adhesive Competence Center & Laboratory

Poznań

Phone +48 605 550427 | acc@bm-chemie.pl

ESTONIA / LATVIA / LITHUANIA

Bodo Möller Chemie Baltics OÜ

Tartu (Estonia)

+370 686 82 933 | info-baltics@bm-chemie.com

CZECH REPUBLIC / SLOVAKIA

Bodo Möller Chemie Czech & Slovakia, s.r.o.

Sales Office Bratislava (Slovakia)

Phone +421 2 33006732 | info@bm-chemie.sk

Sales Office Prague (Czech Republic)

Phone +420 239 045301 | info@bm-chemie.cz

HUNGARY

Bodo Möller Chemie Hungary Kft.

Tatabánya

Phone +36 34 782019 | info@bm-chemie.hu

CROATIA

Bodo Möller Chemie Austria GmbH

Podružnica Zagreb

Phone +385 91 2620276 | info-hr@bm-chemie.at

ROMANIA

Bodo Möller Chemie Austria GmbH

Sucursala Bucuresti

Phone +40 314 362203 | info@bm-chemie.ro

TURKEY

Bodo Möller Turkey

Kimya Ürünleri Ticaret Ltd. Şti.

Beyoğlu/Istanbul

Phone +90 212 2437634 | info-tr@bm-chemie.com

RUSSIA

Bodo Möller Chemie Russia LLC

Moscow

Phone +7 495 1396000 | info@bm-chemie.ru

INDIA

Bodo Moeller Chemie India Pvt. Ltd.

Mumbai

Phone +91 22 49741848 | info@bm-chemie.in

CHINA

Bodo Moeller Chemie (Shanghai) Co., Ltd.

Shanghai

Phone +86 21 64750182 | info@bm-chemie.cn

Bodo Moeller Chemie Hong Kong Ltd.

Hong Kong

Phone +86 21 64750182 | info@bm-chemie.hk

THAILAND

Bodo Moeller Chemie (Thailand) Co., Ltd.

Sales Office Bangkok

Phone +66 98 269 6088 | info-th@bm-chemie.com

VIETNAM

Bodo Moeller Chemie Vietnam Co., LTD

Hanoi

+84 9 63 69 45 65 | info-vn@bm-chemie.com

ISRAEL

BM Chemie Israel Ltd.

Tel Aviv-Yafo

Phone +972 36 377366 | info@bm-chemie.co.il

MIDDLE EAST

Bodo Möller Chemie Middle East FZE

Dubai (UAE)

Phone +971 4 8813833 | info@bm-chemie.ae

EGYPT

Bodo Moeller Chemie Egypt SAE

Bodo Moeller Chemie Egypt Import Ltd.

Sales Office Cairo

Phone +20 2 226963-91 / -92/ -93

info@bm-chemie.com.eg

Bodo Moeller Chemie Egypt SAE

Sales Office Alexandria

Phone +20 3 3922061 / +20 3 3903210

info@bm-chemie.com.eg

Production Plant Sadat City

Phone +20 4 82656041 | info@bm-chemie.com.eg

MOROCCO

Bodo Moeller Chemie Morocco SARLAU

Casablanca

Phone +212 522 262732 | info@bm-chemie.ma

KENYA

Bodo Moeller Chemie Kenya Ltd.

Nairobi

Phone +254 788 071608 | info@bm-chemie.co.za

NIGERIA

Bodo Moeller Chemie Nigeria FZE

Lekki Free Zone, Lagos

Phone +971 4 8813833 | info@bm-chemie.ae

SOUTH AFRICA / SUB-SAHARA REGION

Bodo Möller Chemie South Africa (PTY) Ltd.

Sales Office Port Elizabeth

Phone +27 41 3641335 | info@bm-chemie.co.za

Sales Office Johannesburg

Phone +27 114 501745 | info@bm-chemie.co.za

USA

Bodo Moeller Chemie Corp.

Atlanta, Georgia

Phone +1 770 2952288 | info-us@bm-chemie.com

MEXICO

Bodo Möller Chemie México, S. de R.L. de C.V.

Puebla

Phone +52 222 2405168 | info@bm-chemie.mx